

# DATA SHEET

## SSB cold shrink tubing

Item no.: 100021-100023



[www.ssb-electronic.com](http://www.ssb-electronic.com)

- Easy and time-saving installation without tools or heat application
- Protection of connector interfaces against environmental influences and external access
- Very high temperature resistance up to 200°C
- Acid and alkali resistant
- UV and ozone resistant
- RoHS compliant
- Suitable for a wide range of cable sizes and connectors



### Specifications:

Color	black
Material	Silicone rubber
Dielectric strength	21 kV/mm
Electrical resistance	3,4·10 <sup>15</sup> Ω·cm
Shore hardness	44 Shore A
Tear strength	35 kN/m
Tensile strength	10,8 MPa
Elongation at break	750 %
IP protection class	IP 68
Flammability rating acc. to UL94	V-0
Temperature range	-60 to +200 °C

### Available products:

Item number	100021	100022	100023
Inner diameter	28 mm	35 mm	45 mm
Length	125 mm	178 mm	178 mm
Diameter after shrinking	< 6 mm	< 8 mm	< 9 mm
Material thickness after shrinking	3 mm	3,5 mm	3,5 mm
Suitable for following connectors	N BNC TNC UHF SMA	4.3-10 NEX10 N BNC TNC UHF SMA	7-16 DIN 4.3-10 NEX10 N BNC TNC UHF SMA

**Right of technical modification is reserved**

SSB-Electronic GmbH · Am Pulverhäuschen 4 · 59557 Lippstadt · Germany

Status: March 2025