



Standard polyester braided sleeving

Helagaine HEGP

Helagaine HEGP braided sleeving provides abrasion protection in the automotive industry, in machine building, in panel building and in electrical appliances.

Features and benefits

- Made of sturdy polyester
- Highly flexible
- High abrasion resistance
- Very high surface coverage



Helagaine HEGP braided sleeving.

MATERIAL	Polyester (PET)
Operating Temperature	-50 °C to +150 °C
Melting Point	+250 °C
Flammability	UL 94 V2, FMVSS 302



TYPE	Bundle Ø min.	Bundle Ø max.	Colour	Reel Length	Tools	Article-No.
HEGP03	1.0	5.0	Black (BK)	200 m	45	170-10300
HEGP04	2.0	7.0	Black (BK)	200 m	45	170-10400
HEGP05	3.0	9.0	Black (BK)	200 m	45	170-10500
HEGP06	4.0	11.0	Black (BK)	100 m	45	170-10600
HEGP08	5.0	12.0	Black (BK)	100 m	45	170-10800
HEGP10	7.0	15.0	Black (BK)	100 m	45	170-11000
HEGP12	8.0	17.0	Black (BK)	100 m	45	170-11200
HEGP15	10.0	20.0	Black (BK)	100 m	45	170-11500
HEGP20	14.0	26.0	Black (BK)	50 m	45	170-12000
HEGP25	18.0	34.0	Black (BK)	50 m	45	170-12500
HEGP30	20.0	40.0	Black (BK)	50 m	45	170-13000
HEGP40	30.0	50.0	Black (BK)	50 m	45	170-14000
HEGP50	40.0	66.0	Black (BK)	50 m	45	170-15000

Recommended Tools: 45=HSG0. For more information on toolings please go to www.HellermannTyton.com/application-tooling.

All dimensions in mm. Subject to technical changes. Colour grey available on request. Cuts in any lengths. Minimum Order Quantity (MOQ) may differ from package content.

EN 45545-2 **ECE R-118**

Please note: Some or all of the products listed here have these approvals, or have one or more sustainable attributes. Please see our website for the latest details.