



### High-expansion polyester braided sleeving

#### Helagaine HEGPX

Helagaine HEGPX is used whenever a higher expansion rate is required. HEGPX is particularly suitable for use in the automotive industry, panel building and in electrical appliances.

#### Features and benefits

- Made of sturdy polyester
- Highly flexible
- High rate of expansion
- Easy to apply over irregular shapes
- Good abrasion resistance



HEGPX - Expandable abrasion protection sleeve.

<b>MATERIAL</b>	Polyester (PET)
<b>Operating Temperature</b>	-50 °C to +150 °C
<b>Melting Point</b>	+250 °C
<b>Flammability</b>	UL 94 V2, FMVSS 302



TYPE	Bundle Ø min.	Bundle Ø max.	Colour	Reel Length	Tools	Article-No.
HEGPX06	3.0	9.0	Black (BK)	200 m	45	170-00060
HEGPX09	5.0	16.0	Black (BK)	100 m	45	170-00090
HEGPX12	6.0	19.0	Black (BK)	100 m	45	170-00120
HEGPX20	12.0	32.0	Black (BK)	100 m	45	170-00200
HEGPX30	19.0	45.0	Black (BK)	50 m	45	170-00300
HEGPX40	32.0	70.0	Black (BK)	50 m	45	170-00400

Recommended Tools: 45=HSG0. For more information on toolings please go to [www.HellermannTyton.com/application-tooling](http://www.HellermannTyton.com/application-tooling).

All dimensions in mm. Subject to technical changes. Colour grey available on request. Cuts in any lengths. Minimum Order Quantity (MOQ) may differ from package content.

**EN 45545-2**



Please note: Some or all of the products listed here have these approvals, or have one or more sustainable attributes. Please see our website for the latest details.