



**43M-LCF78-E01**

**4.3-10 Male Straight Connector for 7/8" Coaxial Cable, OMNI FIT™ Premium, O-Ring and compression sealing**

OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminium) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment. All RFS connectors are fully tested for mechanical and electrical compliance to industry specifications.

The 7-16 connector is the most rugged RF connection meeting all requirements even under the most severe environmental conditions. Sealing against outer conductor and jacket by means of O-Ring and 360° compression fit.



**FEATURES / BENEFITS**

- Ultra high PIM performance i.e. reduced interference leading to high customer satisfaction
- Two-piece design i.e. visual inspection of interlocking leads to improved installation security
- OMNI FIT™ concept i.e. streamlined order management and reduced stock level
- Watertight sealing in mated and unmated condition, i.e. reduced efforts during installation and improved security during operation
- Tri metal alloy plating i.e. extreme resistance against corrosion even under hardest climatic and environmental circumstances
- Multi-thread (Tristart) design i.e. simplified and accelerated tightening process
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis

**Technical features**

**GENERAL SPECIFICATIONS**

Transmission Line Type		Coaxial Cable
Cable Size		7/8
Cable Type		Foam Dielectric
Model Series		LCF78-50 Series, RCF78-50 Series
Connector Interface		4.3-10
Connector Type		OMNI FIT™ PREMIUM Straight
Sealing Method		Sealing rubber + 360° clamping
Gender		Male

**ELECTRICAL SPECIFICATIONS**

Nominal Impedance, ohms	Ohm	50
3rd Order IM Product @ 2x20 Watts	dBc	-163 ; typical -167
Maximum Frequency	GHz	6.0
VSWR, Return Loss	VSWR (dB)	0 &lt; f ≤ 1.0 GHz: 1.02 (40) 1.0 &lt; f ≤ 2.2 GHz: 1.03 (37) 2.2 &lt; f ≤ 2.7 GHz: 1.03 (36) 2.7 &lt; f ≤ 3.8 GHz: 1.06 (31) 3.8 &lt; f ≤ 5.0 GHz: 1.11 (26) 5.0 &lt; f ≤ 6.0 GHz: 1.15 (23)

**MECHANICAL SPECIFICATIONS**

Plating Outer/Inner		NiTIn/Silver
Length	mm (in)	74 (2.91)
Outer Diameter	mm (in)	37 (1.46)
Inner Contact Attachment		Spring finger
Outer Contact Attachment		360° clamping



**43M-LCF78-E01**

4.3-10 Male Straight Connector for 7/8" Coaxial Cable, OMNI FIT™ Premium, O-Ring and compression sealing

**ACCESSORIES**

<b>Wrench size front</b>	mm (in)	34 (1,34)
<b>Wrench size rear</b>	mm (in)	34 (1,34)
<b>Trimming Tool</b>		TRIM-SET-L78-D01, TRIM-LCF78-D01-A

**TESTING AND ENVIRONMENTAL**

<b>Waterproof Level</b>		IP68
-------------------------	--	------

[External Document Links](#)  
[Installation Instruction](#)

[Notes](#)