

DATASHEET

FO 1x12 50/125 MM OM5 CST 9,0 mm DNV

Item no.: 2046



www.ssb-electronic.com

Description

Universal optical fiber central loose tube (jelly filled) cable with glass yarns as strength member, corrugated steel tape armor and low smoke zero halogen outer jacket. This cable has improved rodent protection by corrugated steel tape.



Applications

For outdoor and indoor use in structured (data) wiring systems such as industrial backbone, campus backbone, building backbone (riser) and/or horizontal cabling. For outdoor and indoor use in networks for industrial, telecom, cable TV and/or broadcast. Easy to install in ducts, tunnels and trenches and/or tubes. Suitable for direct burial. The cable has DNV approval for marine and offshore applications.

Construction

Construction type	Central loose tube (CLT)
Fiber type	Multimode OM5
Fiber count	12
Fiber color coding	Blue, orange, green, brown, gray, white, red, black, yellow, violet, pink, aqua
Subunit	1 tube gel filled
Subunit Ø	3,3 mm
Fiber core diameter	50 µm
Strength member	Glass yarns waterblocking
Type of armor	Corrugated steel tape (CST) full rodent protected
Jacket	LSZH halogen-free, flame retardant (black)
Outer diameter	9,0 mm

Optical characteristics

Max. attenuation	1300 nm: 0,90 dB/km 850 nm: 2,9 dB/km
------------------	------------------------------------------

Technical data

Weight	104 kg/km
Temperature range	Installation: -5 °C to +50 °C Operation: -30 °C to +70 °C
Min. bend radius	Short term: 180 mm Long term: 180 mm
Max. tensile strength	Short term: 760 N (171 lbf) Long term: 500 N (112 lbf)
Max. crush resistance	Short term: 22 kN/m Long term: 11 kN/m
Approvals	DNV
Standards	IEC 60794-1-21, IEC 60794-3-10, IEC 60332-1-2/22, IEC 60331-25-E120 / EN 50200-PH120 ANNEX E, IEC 60754-1/2, IEC 61034-2, ISO/IEC 11801-1
REACH	Compliant
EU Directive 2011/65/EU (RoHS 2)	Compliant
UV / Sunlight protection	Yes